


# **Summit TRTL30x6 by Bischoff**



Size 6021



**Bischoff**

*Bischoff Security U.S.A.*

*Where Diamonds And Security All Began . . .  
Insurance Approved For Upgrading Your Security*



The safe manufactured where diamonds and security all began . . .

## Bischoff TRTL30x6

### Introducing the Summit TRTL30x6

Manufactured for the high-security market, the Summit is the first safe to use special Super-Alloy from Bischoff. This Super-Alloy incorporates multiple layers of stainless steel, aluminum alloy, copper, and Bischoff's own special alloy spheres.

The Summit safe, using Bischoff's special Super-Alloy, gives six-sided protection for locations with severe elevator and floor-load restrictions. Bischoff is truly the problem-solver.

#### DOOR SPECIFICATIONS

The overall door thickness is 220 mm (8.5"), and is constructed of outer and inner plates that contain alloy thickness of 100 mm. Additional protection is provided by a frame of copper bars in the door and jamb area.

#### BODY SPECIFICATIONS

The body features a one-piece bell casting of Super-Alloy by Bischoff with an overall thickness of 110 mm with an alloy thickness of 100 mm.

#### LOCKS

The Summit is equipped with two U.L.-listed group 1 manipulation-proof locks. A third lock, a nine-lever, double-bitted keylock is provided in conjunction with the combination locks. All models are prepared for time locks, with the exception of the smallest two units.

#### BOLTWORK

The massive boltwork and locking systems were designed to give maximum protection against explosive attacks from all directions. The Summit has a three-way moving boltwork, with fixed bolts on the hinge side of the door. The diameter of each bolt is a massive 39mm (1 1/2").


#### RELOCKING DEVICES

The relocking devices and vital mechanisms are protected by special glass plates, which if tampered with, release a number of randomly-located relocking devices, independent of the exterior locks. This provides the safe with maximum protection against invasion. Live relocking devices are used so that they activate each time the safe is locked.

## Bischoff



The Bischoff Safe & Electro Security Group



MODEL	INSIDE DIMENSIONS inches			OUTSIDE DIMENSIONS inches			CUBIC INCH CAPACITY	APPROX. TOTAL WEIGHT
	HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH		
SM2517	25	17	18	32 1/4	25 1/4	20 1/4	980	15 1/2 lbs
SM3620	36	25	20	44 1/4	28 1/4	22 1/4	1400	22 1/2 lbs
SM4820	48	28	25	56 1/4	28 1/4	22 1/4	1700	28 1/2 lbs
SM6021	60	31	21	68 1/4	28 1/4	22 1/4	2600	42 1/2 lbs
SM6826	68	36	20	76 1/4	34 1/4	22 1/4	3500	52 1/2 lbs
SM6836	68	36	20	76 1/4	44 1/4	22 1/4	4300	72 1/2 lbs

OVERALL DOOR THICKNESS TRTL30x6 — 8 1/2 inches

ALLOY THICKNESS TRTL30x6: DOOR — 3 1/4" BODY — 3 1/4"

All Dimensions and Weights are Approximate