


**CHATWOOD-MILNER**

**MONARCH**

**MONEY AND JEWELLERY SAFES**

**OXYACETYLENE    EXPLOSIVE  
AND DRILL RESISTIVE**



Modern techniques versus modern criminals, that is the philosophy behind the Chatwood Milner Monarch Acme Safe. It is a safe which will resist all forms of attack, for today's safebreaker is practised in up-to-the-minute metal cutting techniques, skilled in the use of explosives and an experienced operator with an armoury more extensive, lethal and scientific than ever before.

It is science that has given the safecracker these new opportunities and it is science that has given the safemaker the means to combat them.

The Chatwood Milner Monarch Acme Safe is the product of exhaustive research into protective materials and techniques. The core of its protection is Chatwood Milner torch and drill resisting armour, a composite with a matrix of thermal strength and toughness incorporating inclusions to resist drilling.

Advanced manufacturing techniques have enabled Chatwood Milner engineers to produce a safe body in a single cast unit of consistent strength. Added to this is Chatwood Milner isolator boltwork, a revolutionary design of locking mechanism, which not only provides highly sophisticated drill protection but incorporates advanced techniques for protection against explosive attack.

## SPECIFICATION

**Door**  $7\frac{1}{2}$ in thick and rectangular the door is constructed from outer and inner steel plates continuously welded to form a single structure and enclosing a 2in thick solid layer of Chatwood Milner torch and drill resisting armour to produce a total metal thickness of  $2\frac{1}{2}$ in. The total strength of this door is to effectively resist electric drills, oxy-acetylene torches, forcing tools, sledgehammers and explosives. The boltwork chamber is protected over its whole area by torch and drill resisting armour, the whole making up a super burglar resistive door.

**Body** By enclosing a 2in thick solid layer of torch and drill resisting armour which has been cast into (1) piece in a steel outer and inner lining Chatwood Milner engineers have produced a safebody of exceptional strength. This 2in thick solid layer of torch and drill resisting armour cast in one (1) piece eliminates the necessity of welding five (5) slabs of material together to form a body. Welded slabs produce weak welded seams. The Chatwood Milner one (1) piece cast construction has no weak welded seams. This one (1) piece construction eliminates the possibility of de-slabbings the entire top, sides, bottom or back of the safe as is possible with a safe manufactured with slab construction. This construction also eliminates the possibility of weak seams splitting open when explosives or wedges are used because Chatwood Milner construction does not produce a slab constructed safe with weak welded seams. *We would appreciate the chance to review this important feature with you.*

**Boltwork**  $1\frac{1}{2}$ in diameter steel sliding bolts extend from all four (4) sides of the door to ensure a solidarity with the body. The 2in thick solid layer of torch and drill resisting armour protects the boltwork and locking mechanism from every angle. On closing the combination lock or keylock the internal boltwork mechanism is disconnected from the external turn handle. The handle revolves free as though it were broken, without any possibility of re-engaging the internal boltwork mechanism until the proper combination numbers are used to open the combination lock and the proper key used to open the keylock. Any attempt to force an entry by dislodging the combination lock or keylock is thereby defeated since with the handle and boltwork system disconnected from one another there is no means of retracting the four (4) way boltwork system. Also by dislodging the combination lock and keylocking mechanisms or cutting the holding arms to the boltwork frames, the internal boltwork system relocks within itself not allowing the bolts to be withdrawn into an open position. Relocking devices are incorporated in the locking system to ensure that the bolt throwing mechanism remains positively locked in the extended position under various types of burglary attack. *We would appreciate the chance to review this important feature with you.*

**Combination Lock with spy proof dial** Five (5) movement spy proof dial combination lock is capable of 100,000,000 different combination changes. It is virtually pick proof. The spy proof dial design prevents unauthorised individuals from seeing the numbers dialled when you are operating the dial to unlock the combination lock.

**Dial Check Lock** You can keylock the dial in the combination lock in the open or closed position. This prevents the dial from being moved. During the day when the combination lock is in the open position the dial cannot be turned and thereby the safe accidentally locked. When you close the combination lock, upon leaving the premises, you can again lock the dial so that it cannot be turned by any unauthorised intruders who may try to manipulate the lock.

**Change your own combination - whenever you wish** Since security is the prime purpose of this safe, the combination is set by the individual responsible for the contents of the safe. No unauthorised person should know the combination numbers. We supply simple written instructions to you so that you can change your own combination at regular intervals.

**Keylocking lock** This lock is a double bitted keylock with ten (10) tumblers. This is a key retaining lock which means that the key cannot be withdrawn from the lock unless the bolts are thrown into a closed position and the key turned to a locked position. This ensures that the key cannot be removed from the lock unless the locking mechanisms are locked. This prevents you from accidentally removing the key from the keylock while the lock is in the open position and leaving the premises. Ten (10) tumblers on a keylock is like having ten (10) numbers to open a combination lock. This lock is virtually pick proof.

**Important** When leaving the premises be certain that the combination lock and the keylock are locked. Do not assume that when either lock is locked that it is doing the same job as when both locks are locked.

**Smoke Detection** Due to the type of materials used in the construction of this safe a great deal of smoke is produced when heat is applied. This heavy smoke is disagreeable to the burglar and if the smoke detection alarm is in use, it should automatically operate.

**Time Lock** of 2 or 3 movement 120 hour design can be incorporated in the locking mechanism. The time lock operates independently of any other locking mechanism in the safe. Preset to go off at a selected time the lock prevents the safe from being opened until the correct time is reached even if the other locking mechanisms have been unlocked. (Optional equipment).

**Cupboards** Cupboards are constructed of sheet steel suitably reinforced and secured by a keylock with keys in duplicate. The internal height of the cupboard can be made to suit your exact requirements. The most common sizes are 12in and 15in high inside. The overall width of all cupboards is 1in less than the internal width of the safe, the overall depth of all cupboards being 1in less than the internal depth of the safe (optional equipment).

**Fittings** The fitting supports are formed in the sides of the lining, the fittings being designed so that they can be adjusted at  $1\frac{1}{4}$ in intervals. The drawers are of steel secured by a keylock with keys in duplicate. The drawers are mounted between two shelves secured to the supports by vertical clips. They are supplied either as one full-width drawer or two drawers side by side. The shelves are of sheet steel flanged and secured to the support by clips (optional equipment).


## Size of Drawers

	inside size of drawer		
	high	wide	
		full width	half width
221515	4in	13 $\frac{1}{2}$ in	6 $\frac{1}{2}$ in
342019/4620	4in	18 $\frac{1}{2}$ in	8 $\frac{1}{2}$ in
552019	4in or 6in	18 $\frac{1}{2}$ in	8 $\frac{1}{2}$ in
642817/21	6in		13 $\frac{1}{2}$ in
	fitment overall		
	deep	high	
221515	12 $\frac{1}{8}$ in	5 $\frac{1}{2}$ in	
342019/4620	16 $\frac{1}{8}$ in	5 $\frac{1}{2}$ in	
552019	16 $\frac{1}{8}$ in	7 $\frac{1}{2}$ in	
642817	14 $\frac{1}{8}$ in	7 $\frac{1}{2}$ in	
642821	18 $\frac{1}{8}$ in	7 $\frac{1}{2}$ in	

## FINISH

The Monarch Acme safe is finished in 2-tone grey. Medium grey body - light grey door.

The furniture is mounted on a stainless steel panel complete with stainless steel pull handle.



## INTERNAL AND EXTERNAL DIMENSIONS OF THE 'MONARCH ACME' SAFES

DIMENSIONS ARE IN INCHES

MODEL	OUTSIDE DIMENSIONS					INSIDE DIMENSIONS			FOR SWING			OVERALL SIZES DOOR OPEN		
	Height A	Width B	Depth of Body C	Depth over Hinge D	Depth over Handle E	Height F	Width G	Depth H	K	L	M	N	P	Q*
221515	31	24 1/2	26 1/2	28 1/2	29	22	15	15	27 3/8	1 1/2	20 1/2	48 1/8	44	37
342019	43	29 1/2	30 1/2	32 1/2	33	34	20	19	31 1/8	1 1/2	25 1/2	57 1/8	54	45 1/2
462019	55	29 1/2	30 1/2	32 1/2	33	46	20	19	31 1/8	1 1/2	25 1/2	57 1/8	54	45 1/2
552019	64	29 1/2	30 1/2	32 1/2	33	55	20	19	31 1/8	1 1/2	25 1/2	57 1/8	54	45 1/2
642817	73	37 1/2	28 1/2	30 1/2	31	64	28	17	29 1/8	1 1/2	33 1/2	63 1/8	70	58 1/2
642821	73	37 1/2	32 1/2	34 1/2	35	64	28	21	33 1/8	1 1/2	33 1/2	67 1/8	70	58 1/2

\*Door opened to give full width access to interior of safe

MODEL	Approx. Cu. Cap.
221515	2-87 ft 4950 in
342019	7-47 ft 12920 in
462019	10-1 ft 17480 in
552019	12-1 ft 20900 in
642817	17-63 ft 30464 in
642821	21-76 ft 37632 in

# CHATWOOD-MILNER

## MONARCH RECTANGULAR DOOR COFFER

The Chatwood-Milner Coffers has been designed to provide the most modern burglary protection. By fitting the coffer, within a fire-resistive safe being used for the protection of records, the coffer would then provide the necessary protection for cash and valuables. The coffer can also be enclosed in a steel clad concrete block to suit any dimensions as a free standing unit. The purpose of the steel cladding filled with concrete is to give additional weight to the coffer so that the unit will be much heavier and therefore much more difficult for the burglar to remove from the premises. The coffer embodies the latest type of Chatwood-Milner locking mechanisms and armour resistant to oxyacetylene torch, explosives, drills and sledge hammers.

### SPECIFICATIONS

**Door** 5 inches thick and rectangular the door is constructed from outer and inner steel plates continuously welded to form a single structure and enclose a 2½ inch thick solid layer of Chatwood-Milner torch and drill resisting armour to produce a total metal thickness of 3 inches. The total strength of this door is to effectively resist electric drills, oxyacetylene torches, forcing tools, sledge hammers and explosives. The boltwork chamber is protected over its whole area by torch and drill resisting armour making up a super burglar-resistant door.

**Body** By enclosing a 2 inch thick solid layer of torch and drill resisting armour which has been cast in one (1) piece in a steel outer and inner lining. Chatwood-Milner engineers have produced a safe body of exceptional strength. This 2 inch thick solid layer of torch and drill resisting armour cast in one (1) piece, eliminates the necessity of welding five (5) slabs of material together to form a body. Welded slabs produce weak welded seams. The Chatwood-Milner one (1) piece cast construction has NO WEAK WELDED SEAMS. This one (1) piece construction eliminates the possibility of de-slabbng the entire top, sides, bottom or back of the safe as is possible with a safe manufactured with slab construction. One (1) piece cast construction also eliminates the possibility of weak seams splitting open when explosives or wedges are used. We would appreciate the chance to review this important feature with you.

**Boltwork** Six (6) sliding bolts measuring 1½ inch diameter, provides three (3) top and three (3) bottom. Bolts are fully protected by the 2½ inch special armouring in the door and 2 inch special armouring in the body and the bolts become an integral part of the special armouring.

**Combination Lock** Five (5) movement—spy-proof dial with dial check lock. For security reasons we shall not describe the mechanisms of this lock, however, we shall be pleased to give you further information upon request. This five (5) number combination lock makes it virtually impossible for even the most skilled professional safe expert to manipulate the combination. Since security is the prime purpose of this safe, the combination is set by the individual responsible for the contents. No outside person should know the combination numbers. We supply simple written instructions to you so that you can change your own combination at regular intervals.

**Relocking Device Bolt** An additional trigger bolt is incorporated to provide further protection against explosives, oxyacetylene torches, drills and sledge hammers.

Chatwood-Milner policy is one of constant improvement. We therefore reserve the right to alter any part of the specification outlined above without incurring any obligation.



### DIMENSIONS

Model	Outside dimensions			Inside dimensions			Cubic Capacity
	Height	Width	Depth	Height	Width	Depth	Feet and Inches
12149	17"	19½"	17½"	12"	14½"	9½"	.99 1704

Overall Depth 18½" (door open at 90°)

Clear Door opening - 9½" high x 9½" wide

\*Deduct 1" from portion of inside depth for protrusion of combination lock tumbler case which measures 4½" high x 7" wide.