



**RATNER trustee 5000 and
executive 2500**

Specifications

TRUSTEE 5000 SAFE

This new Ratner Trustee is the latest development in the line of well tried and highly successful Trustee models.

Incorporated in both door and body is reinforced Ranaloy, which provides resistance to attack from oxy-acetylene cutting tools and drills. The non-metallic anti-penetration monolith surrounding the Ranaloy gives additional protection against attacks by force, hand tools and flame cutting plus a high degree of fire protection for the safe contents.

Body

The outer body is formed from high quality $\frac{1}{4}$ " (6 mm) tough steel plate electrically welded. Enclosed by the outer body is a non-metallic reinforced monolith which in turn encases the Ranaloy protection. A further $\frac{3}{8}$ " (4.7 mm) steel casing welded around the slotted steel inner lining, completes the inner body. The total metal protection is not less than $1\frac{1}{2}$ " (32 mm), in a body thickness of 4" (102 mm).

Door

The Ratner Trustee 5000 has a recessed door giving strength as well as an exclusive and modern appearance.

Overall thickness of the door is $4\frac{1}{2}$ " (115 mm). The main protective slab, covering the entire lock and boltwork area, comprises $2\frac{1}{2}$ " (57 mm) of metal consisting of a $\frac{3}{8}$ " (9.4 mm) front steel plate, not less than $1\frac{1}{4}$ " (32 mm) Ranaloy protective slab and a $\frac{3}{8}$ " (9.4 mm) duplex steel plate plus additional mount plate.

Boltwork

A unique 3-way sliding boltwork system plus fixed dog bolts on hinge side of door provides resistance against explosives and forcing attacks.

The number of bolts varies according to the size of safe.

Locking

The boltwork is controlled by a Ratner 10-lever high security keylock with detachable bitted stainless steel keys in duplicate.

The lock is mounted on a sensitive plate which responds to any form of attack in the lock area and actuates one or more of the Ratnermatic devices, whose positions can be varied.

A second keylock can be fitted if required. Alternative locking can be provided by means of a 4-wheel combination lock.

Anti-explosive devices

Both live and dead Ratnermatic anti-explosive devices are fitted. The live Ratnermatic is brought into play every time the safe is locked to ensure that the bolts are independently secured should the main lock be disturbed by explosives or other means.

The Ratnermatic has been independently tested by the Nobel Division of Imperial Chemical Industries Ltd., a copy of whose report will be sent on request.

An additional thermal re-locking device actuated by heat is incorporated in all sizes other than size 17.

Fittings

Adjustable shelves, at 1" (25 mm) centres, are available for all sizes.

A 3" (76 mm) drawer is available for all sizes, a 6" (152 mm) drawer is available for all sizes except Size 17.

A 12" (305 mm) cupboard is available for Sizes 35 and 50.

All drawers and cupboards provided with key-lock with keys in duplicate.

Anchoring

Facilities are provided as standard and it is strongly recommended that these facilities are used.

EXECUTIVE 2500 SAFE

Similar to the New Trustee Safe except that:—

- (1) Body does not contain Ranaloy.
- (2) Body total metal thickness, approx $\frac{1}{2}$ " (12 mm), with a reinforced fire, drill and hand tool resistant, monolith not less than 3" (75 mm) thick.

The Executive 2500 has the same high quality drill and blowtorch resistant door as the Trustee, including multiple re-locking devices, as described above. Thus it gives the maximum protection where it is most needed and in the favourite spot for burglary attack—the safe door and front frame.

Finish

Both the Trustee 5000 and the Executive 2500 safes are impressively finished in dark grey enamel.

Dimensions

Trustee 5000 Safe

Size	External Dimensions			Internal Dimensions			Capacity	Weight
	Height	Width	Depth *	Height	Width	Depth		
17	25" 635 mm	19" 485 mm	19 $\frac{1}{8}$ " 505 mm	17" 430 mm	11" 280 mm	9 $\frac{3}{8}$ " 250 mm	1.20 cu ft 34.00 ltrs	7 $\frac{1}{2}$ cwts 370 kg
23	31" 790 mm	22 $\frac{1}{2}$ " 570 mm	26 $\frac{1}{8}$ " 680 mm	23" 585 mm	14 $\frac{1}{2}$ " 370 mm	16 $\frac{3}{8}$ " 425 mm	3.00 cu ft 85.00 ltrs	13 cwts 662 kg
35	43" 1095 mm	28" 710 mm	29 $\frac{1}{8}$ " 760 mm	35" 890 mm	20" 510 mm	19 $\frac{3}{8}$ " 500 mm	8.00 cu ft 230.00 ltrs	21 $\frac{1}{2}$ cwts 1082 kg
50	58" 1475 mm	28" 710 mm	29 $\frac{1}{8}$ " 760 mm	50" 1270 mm	20" 510 mm	19 $\frac{3}{8}$ " 500 mm	11.50 cu ft 326 ltrs	29 $\frac{1}{2}$ cwts 1502 kg

Executive 2500 Safe

Size	External Dimensions			Internal Dimensions			Capacity	Weight
	Height	Width	Depth *	Height	Width	Depth		
17	25" 635 mm	19" 485 mm	19 $\frac{1}{8}$ " 505 mm	17" 430 mm	11" 280 mm	9 $\frac{3}{8}$ " 250 mm	1.20 cu ft 34.00 ltrs	6 $\frac{1}{2}$ cwts 320 kg
23	31" 790 mm	22 $\frac{1}{2}$ " 570 mm	26 $\frac{1}{8}$ " 680 mm	23" 585 mm	14 $\frac{1}{2}$ " 370 mm	16 $\frac{3}{8}$ " 425 mm	3.00 cu ft 85.00 ltrs	11 $\frac{3}{8}$ cwts 598 kg
35	43" 1095 mm	28" 710 mm	29 $\frac{1}{8}$ " 760 mm	35" 890 mm	20" 510 mm	19 $\frac{3}{8}$ " 500 mm	8.00 cu ft 230.00 ltrs	19 $\frac{3}{8}$ cwts 1009 kg
50	58" 1475 mm	28" 710 mm	29 $\frac{1}{8}$ " 760 mm	50" 1270 mm	20" 510 mm	19 $\frac{3}{8}$ " 500 mm	11.50 cu ft 326 ltrs	27 $\frac{3}{8}$ cwts 1412 kg

* N.B. Add 1 $\frac{1}{2}$ " for overall depth inclusive of hinges and handle on all models

The aim of the Ratner Safe Company is always to provide the best in security, therefore we reserve the right to incorporate any improvements and alter any specification accordingly without prior notice.

By virtue of the Trade Descriptions Act 1969, all measurements must necessarily be considered to be approximate.

