



International Mark IV
(US. UL. TL. 15)

The latest development in a series of high quality, light range safes, the SLS International Model 1812 offers improved specification to protect moderate amounts of cash and valuables against attack by force, drills and explosives on the body, in addition to the protection against oxygen/hydro attack in the door hinged areas. The inclusion of a zirconium alloy casting in the door together with SLS patented 'Supermetal' pins greatly increased drill protection over the vitreous enamel. The SLS enclosed construction is designed to ensure rigid protection for cash and valuables.

Protection: In four areas, the SLS International Model 1812 offers complete facilities of protection against: burglary, fire, gas, and explosion - for cash and valuables.

Safe Body: The safe body has been forged and constructed from 4 1/2" (115mm) mild steel and finished with Vitreous Enamel coating to the inside and outside surfaces of 2500 K² m².

Safe Door: The door is made from 1 1/2" (38mm) 304 and 316 stainless steel to the inside and 1 1/2" (38mm) mild steel to the outside, finished with SLS Supermetal pins and pins of 1 1/2" (38mm) diameter.



Typical Underpinning Lab. Test Attack

FEATURES

Body: Built to the same standard as the Model 1812, the SLS International Model 1812 is built to the same standard as the Model 1812.

Locking: Locking can be fitted to SLS 74 for multiple locking. The SLS 74 is a high security locking system. These tests are interchangeable and dual locking can be supplied.

Re-locking Devices: A five relocking devices fitted.

Floor Anchoring: Every safe is prepared with a base fixing bolt to a 4 1/2" (115mm) diameter high tensile bolt suitable for either concrete or wood floors.

Fittings: A full range of safe furniture, 10" shelves, lockable full width and half-width drawers and lockable cupboards is available.

Independent Fire Test: A one-hour fire test was successfully achieved at Worthington Research Centre (Test Ref: W.R.C.S.I. No 22854/6).



Model 1812



Model 2316



Model 3520



Model 5020

	Model 1812	Model 2316	Model 3520	Model 5020
EXTERNAL - INS	25 19 17	30 23 24	42 27 25	52 31 29
INTERNAL - INS	18 12 9	23 16 16	35 26 19	50 26 19
LBS	686	1130	1790	2450

Additional 1/2" in total depth over handle

SLS now has the right to incorporate improvements and other specifications as technology advances and to do so without notice.

MEGASAFE
HIGH SECURITY SAFES
(800) 345-6552 www.megasafe.com