

# INTERSEC

## Nordic Mini Vault

TRTL 30




 **Tann**

# INTERSEC Nordic Mini-Vault TRTL-30

6-Sided protection against all known forms of attack including. . .

- Explosives
- High speed carbide drills
- Oxy-arc
- Wedging
- Oxy-acetylene
- Heavy hand tools

PLUS: **2-Hour Official Fire Protection label.**



For businesses requiring burglary and fire protection in a large capacity unit, the **Nordic Mini-Vault** is the answer!

The **Mini-Vault** not only meets the specifications of the Bank Protection Act, but by passing the rigorous tests of both Underwriters' Laboratories and the Swedish Standards Association, it rightly earns its position as one of the highest rated security units in the world! The **Mini-Vault** bears the **UL TRTL-30** label and qualifies for the National Bureau of Casualty Underwriters Insurance rate "H" under Mercantile Safe policies, and rate "G" for Broad Form and Bank policies. The **Nordic Mini-Vault** also displays the **Class A 120** certification by the Swedish Standards Association recognizing officially tested fire resistance for a duration of 2 hours in a furnace with temperatures up to 1850° F. (1010° C.)

The **Nordic Mini-Vault** is, as its name implies, large enough to accommodate safe deposit boxes, teller lockers and cash lockers or large jewelers' trays.

### DIMENSION (INCHES)

Model No.	INTERNAL			EXTERNAL			Approx. Weight LBS.
	High	Wide	Deep	High	Wide	Deep	
MV4739	70	36	24½	83½	47		

### Construction:

#### Door:

Security is immediately evident in the design of the **INTERSEC Nordic Series**. The massive 5-¼ inch thick rectangular door is recessed within the body of the vault to resist prying and tool assaults. Unlike most vault doors, the hinges are not exposed to potential attack, but are actually an integral part of the safe's body. The door itself comprises an extremely tough alloy and massive monolithic barrier designed to resist all known types of attack including torch, tools and high-speed drills. Additional door security includes the use of glass mounted anti-explosive, drilling and thermal relocking devices, Sargent & Greenleaf (Group 1) tamper-resistant, manipulation proof combination locks and four-way boltwork.

#### Locking:

Standard on the **Nordic Mini-Vault** are two (2) Sargent & Greenleaf (Group 1) tamper-resistant, manipulation proof combination locks and four-way boltwork.

#### Body:

The body construction of the **INTERSEC Nordic** is specially designed to resist delamination and attack by incorporating a strongly reinforced steel grid of rod and Z-bars. Also within the body's 5 inch thick walls are special alloys and an extra-dense ceramic material to thwart all known forms of assault.

#### Anchoring:

Each safe is designed with the facility to incorporate full security anchorage if desired.

#### Alarm:

Provision for alarm is provided as standard.

#### Finish:

The **INTERSEC Nordic Series** is beautifully finished in a textured sand-grey with steel-blue fascia and polished chrome fittings.



An impressive steel grid forms just one of the many lines of defense in the body build-up completely shrouding the main dense monolithic core of aluminum corund casting.

In a continuing effort to improve our products and meet the changing requirements, we reserve the right to make changes without notice in specifications, models and design.

MANUFACTURED IN SWEDEN BY THE JOHN TAMM SECURITY GROUP.

Distributed by:

**MEGASAFE**  
HIGH SECURITY SAFES  
(800) 345-6552    www.megasafe.com